

## FOAM HOSE REEL STATION



This hose reel station is complete with 1-1/2" x 30M rigid hose, 120L AFFF foam, stainless steel foam concentrate storage tank, 95GPM foam inductor and nozzle. A bypass loop is provided for water or foam discharge.

### STANDARD FEATURES

- Inlet connection : 1-1/2" ANSI 125 RF flange
- Hose reel construction : Aluminium
- Tank Construction : Stainless Steel
- Water/foam pistol grip nozzle
- Non-ferrous piping and fittings
- 120L AFFF foam and concentrate
- 1-1/2" control valve
- Stainless steel pickup tube
- 100mmØ opening hole for foam concentrate filling
- Adjustable foam concentrate 3% to 6%

### APPLICATION:

Protection of oil storage installation loading stations, paint and solvent stores.

|         |                  |
|---------|------------------|
| Code No | FOS070-SS-STD-RD |
|---------|------------------|

## FOAM STATION CABINET



This hose reel station is complete with 1-1/2" x 30M rigid hose, 120L AFFF foam, stainless steel foam concentrate storage tank, 95GPM foam inductor and nozzle. A bypass loop is provided for water or foam discharge.

### STANDARD FEATURES

- Inlet connection : 1-1/2" ANSI 125 RF flange
- Hose reel construction : Aluminium
- Tank Construction : Stainless Steel
- Cabinet Construction : Mild steel or Stainless Steel (upon request)
- Water/foam pistol grip nozzle
- Non-ferrous piping and fittings
- 120L AFFF foam and concentrate
- 1-1/2" control valve
- Stainless steel pickup tube
- 100mmØ opening hole for foam concentrate filling
- Adjustable foam concentrate 3% to 6%

### APPLICATION:

Protection of oil storage installation loading stations, paint and solvent stores.

|         |                  |
|---------|------------------|
| Code No | FOS089-MS-STD-RD |
|---------|------------------|



### STANDARD FEATURES

- 2 nos (2-1/2") 65mm x 30m fire hose (Type 1) with Aluminium Alloy BS coupling.
- 140 L AFFF foam in fibre glass tank.
- 2" Gate valve
- Low expansion foam branchpipe 225LPM
- Stainless steel pickup tube
- 100mmØ opening hole for foam concentrate filling
- 225LPM foam inductor adjustable 3% to 6% foam concentrate
- Inlet connection: 2" BSP Male thread

### TECHNICAL SPECIFICATION

- Dimension : 1500.0mm x 1100.0mm x 500.0mm
- Material : Mild steel for cabinet
- Thickness : 1.5mm
- Installation : Floor Mounted
- Capacity : 140 litre foam with Inductor with 2 - 1/2" x 30m hose Type 1 (2 lengths) and Foam branchpipe
- Paint Finish : Epoxy Powder Red

|         |                  |
|---------|------------------|
| Code No | FOS087-MS-STD-RD |
|---------|------------------|