

## CARBON DIOXIDE FIRE EXTINGUISHER ON TROLLEY



Carbon dioxide fire extinguisher on trolley is made of seamless Manganese steel to withstand high storage pressure. It is effective on class B and class C fires and electrically non-conductive.

Carbon dioxide fire extinguisher on trolley is used throughout industry as a protection against industrial fires involving dangerous chemical and gas. Carbon dioxide does not deteriorate with storage or freeze in the container. Carbon dioxide disperses without leaving any contamination or corrosive residue and will not damage valuable equipment and materials.

|                                  | FEX079-CS-450-RD               | FEX079-CS-320-RD |
|----------------------------------|--------------------------------|------------------|
| Capacity, Kg                     | 45                             | 32               |
| Working pressure, Bar            | 60                             | 60               |
| Cylinder test pressure, Bar      | 250                            | 250              |
| Approx. time of discharge, sec   | 75                             | 60               |
| Discharge hose (diameter/length) | 1/2"Ø x 6m                     | 1/2"Ø x 6m       |
| Overall height, mm               | 1600                           | 1420             |
| Overall width, mm                | 2000                           | 2000             |
| Overall depth, mm                | 1170                           | 1170             |
| Full weight, Kg (lb)             | 150 (330)                      | 112 (246)        |
| Material of cylinder             | Manganese Steel BS 5045 Part 1 |                  |
| Paint Finish                     | Grey or Red                    |                  |
| Class of Fire                    | B, C                           |                  |



|                                  | FEX079-CS-150-RD               | FEX163-CS-150-RD        |
|----------------------------------|--------------------------------|-------------------------|
| Capacity, Kg                     | 15                             | 15 x 2 pcs              |
| Working pressure, Bar            | 60                             | 60                      |
| Cylinder test pressure, Bar      | 250                            | 250                     |
| Discharge hose (diameter/length) | 1/2"Ø x 6m                     | 1/2"Ø x 6m              |
| Overall height, mm (approx.)     | ±1050                          | ±2410mm Extended 2780mm |
| Overall width, mm (approx.)      | ±490                           | ±670mm                  |
| Overall depth, mm (approx.)      | ±360                           | 530mm                   |
| Material of cylinder             | Manganese Steel BS 5045 Part 1 |                         |
| Paint Finish                     | Red                            |                         |
| Class of Fire                    | B, C                           |                         |

Optional: Other sizes of CO<sub>2</sub> cylinder available upon request.

The products specified in this brochure are subject to continual development and improvement. Information in this brochure is subject to alteration without notice. All dimensions in mm unless otherwise specified.